

Resistance Standards Catalog

Manufacturing World Class Calibration Standards













Praveen Jain, B.E. CEO



Siddharth Jain, M.B.A **Director Operations Overseas**

Welcome to Vaiseshika®

I am happy to present the latest catalogue of VAISESHIKA Resistance Calibration Standards. We are offering calibration standards catering to the physical parameters of resistance & temperature, instruments encompassing the fields of sound, light intensity, relative humidity, optical, analytical and agri-electronics instrumentation.

The products, showcased in this catalogue, are representing the best manufacturing capabilities and state-of-the-art technologies. All products, are manufactured at Vaiseshika, with purely indigenous technologies, which have been developed and evolved at our manufacturing facility over a long period of research. We have established business partnerships, around the globe, in more than 50 countries, where our Resistance Standards are used by Calibration Labs, Engineering & Oil Industry, Avionics & Master Labs as Master Standards.

Likewise our Master Calibration Standards are compliant to ISO/IEC 17025 Standard and are traceable to the National/ International Standards. We maintain Calibration protocol between Vaiseshika instrument and Reference Calibration Standards. Vaiseshika instruments have been subjected to rigorous in situ trials and are released after successful field trials.

Vaiseshika has developed a strong customer friendly approach for its entire product range with motto "Customer is Supreme". Vaiseshika believes in providing value rich services like operational training and expertise to the customers at our facility. Our engineers conduct training workshops for the customers at thei premises also. Further we maintain and support our customers through service, repair and calibration for a period of more than 10-15 years.


We are confident that our corporate credentials, capabilities, technologies and product range will provide you the confidence and trust of a reliable manufacturer called Vaiseshika Electron Devices.

Praveen Jain (B.E, Aeronautical) CEO










VAISESHIKA MANUFACTURING FACILITY



CALIBRATION FACILITY









INDEX

Sr. No.	CONTENTS	Page No.
1.0	Real Meaning of Calibration	1
2.0	Uniqueness of Vaiseshika Calibration Standards	1-2
3.0	Scope of Accreditation for Electro-technical Parameters	3
4.0	High Precision Decade Resistance Box - Series: 7400	4
5.0	Thumb Wheel Decade Resistance Box - Series: 7400 A	5
6.0	High Precision Decade Resistance Box - Series: 7400 SD	6
7.0	High Value Decade Resistance Box - Series: 8400	7
8.0	Decade Resistor Box - Series: 8400 HVSD	8
9.0	Decade Resistance/ Megohm Box - Series: 7484 HV	9
10.0	Standard Resistor (Oil Cooled / Air Cooled): 9409	10
11.0	Micro & Milli - Ohm Meter Calibrator - Series: 9409 CAL	11
12.0	Fixed Value Insulation Tester Calibration system - Series: 9409 FV	12
13.0	Air/ Oil Cooled DC Shunt - 9410	13
14.0	Decade Capacitance Box - Series: 7500	14
15.0	Decade Inductance Box - Series: 7600	15
16.0	AC/DC High Voltage Probe - 8401	16
17.0	What the Eminent Experts say about us	17
18.0	Prestigious Industrial Organizations in India	17
19.0	Applications of Resistance Calibration Standards in	
	Industry & metrology Laboratories	18-21
20.0	National Awards	22
21.0	Appreciation & Satisfaction Letters	22
22.0	Website View	23
23.0	Spectrum of Optical Instruments	23





REAL MEANING OF CALIBRATION

Vaiseshika Electron Devices manufacture & produce a wide range of Resistance Calibration Standards ranging from \underline{I} micro Ω to 20 tera $\Omega.$ Vaiseshika Resistance Calibration Standards are also accompanid with ISO 17025 Calibration Certificate. The Vaiseshika Metrology Laboratory is fully equipped with in-house ISO/IEC 17025 Compliant Master Calibration Standards.

Calibration is a process wherein your instrument is inspected, assessed and evaluated for its present measurement capability/accuracy. In the process of calibration, we compare the values of measurements of your artefact against a Reference Calibration Standard. If there are deviations (beyond specified accuracy) in your instrument, our engineers adjust, compare and standardize your instrument against our Master Reference Calibration Standards.

Vaiseshika Master Reference Calibration Standards are calibrated at the Government Electronics Research and Testing Laboratories and maintained in our Metrology Laboratory according to ISO 17025 (NABL) protocols. Further our own laboratory is NABL approved.

In ordinary circumstances and with a large number of so called Private Calibration Shops, you only obtain Status Report of your instruments. This means, most of the time, these Makeshift Calibration Shops give you only the results reported in your instrument against casually maintained instrument / makeshift / portable laboratory (sometimes on the back of a bicycle / motorcycle / three wheeler).

UNIQUENESS OF VAISESHIKA CALIBRATION STANDARDS

Whenever you wish to purchase & establish a Master Reference Calibration Standard for your ISO 17025 Accredited Calibration Laboratory, we request you to study the Uniqueness of Vaiseshika Calibration Standards against any other Manufacturer. Vaiseshika provides you the calibration confidence through a Measurement Protocol, documented records & following systematic manner:

- Maintaining Low Drift (18 years span) for Reference Calibration Standards:
 Vaiseshika Metrology Laboratory has been maintaining Master Calibration Standards which have shown Low Drifts of the order of 0.0002 % over a period of 18 years. This low drift of our reference standards have provided high stability to the measurement values thereby ensuring precision & reproducibility of calibrations in Vaiseshika metrology Laboratory.
- 2. Documented Records of Low Drift:
 - Vaiseshika Metrology Laboratory has documented the entire record of drift & stability through a system of regular periodic calibrations of its reference standards at Echelon-II Electronics Regional Test laboratory, Government of India, New Delhi. Further the performance of these Master Standards has been shown & demonstrated to the NABL assessors during their visits on audits at Vaiseshika Metrology Laboratory.
- 3. Calibration is a passion at Vaiseshika & it is your Lifeline:
 - The world of science of measurement and calibration is based on the data that has been collated and gathered by our experts through a well established system of calibration & measurement capability. We ensure precision, repeatability, reproducibility & stability in measurements in our laboratory through a chain of reference calibration standards traceable to the National Physical laboratory, New Delhi.
- 4. Vaiseshika Resistance Calibration Standards fulfills "Make-in-India" Dream of our Hon'ble Prime Minister Narendra Modi by providing World Class Calibration Standards at affordable prices. Some of our Master Standards like 10kV High Resistance Box has components & material withstanding 10kV Voltage during usage, maintaining claimed accuracies & values, which no other manufacturer, in the world is providing. Appreciating Reliability & Durability of our Standards, Leading Calibration Labs & Industrial Companies, around the globe are preferring Vaiseshika Resistance Standards over other leading manufacturers.











MASTER CALIBRATION STANDARD DRIFT & STABILITY CURVE Low Drift and High Stability Curve of our Master Calibration Standards.





- Drift = + 0.0002 %
- Ensuring Precision & Reproducibility of Calibrations (Year 1997 to 2016)
- Demonstrated during all Vaiseshika NABL Certification Audit





Scope of Calibration

Quantity Measured/ Instrument	Range/ Frequency	Calibration Measurement Capability (±)	Remarks
Source Mode	E	lectro Technical Parameter	
DC Resistance	$\begin{array}{c} 0.0001 \ \Omega \\ 0.001 \ \Omega \\ 0.01 \ \Omega \\ 0.1 \ \Omega \\ 1 \ \Omega \\ 10 \ \Omega \\ 100 \ \Omega \\ 1 \ k\Omega \\ 100 \ k\Omega \\ 1 \ M\Omega \\ 10 \ M\Omega \end{array}$	0.015 % 0.015 % 0.015 % 0.015 % 0.004 % 0.004 % 0.004 % 0.004 % 0.004 % 0.004 % 0.004 % 0.004 % 0.004 %	By Direct method
DC Resistance	$0.01~\Omega$ to $100~\text{k}\Omega$ $100~\text{k}\Omega$ to $1~\text{G}\Omega$ $1~\text{G}\Omega$ to $1~\text{T}\Omega$	1% to 0.03% 0.03% to 0.7% 0.7% to 1.5%	By Direct method
Temperature Simulation T/C K-Type J-Type T-Type R-Type S-Type RTD (PT 100)	-200°C to 1368°C -200°C to 1108°C -168°C to 369°C -40.00°C to 1760°C 0°C to 1760°C -190°C to 830°C	2.5°C to 2.1°C 1.1°C to 2°C 1.5°C to 2.1°C 1.5°C to 2.1°C 3.7°C 0.7°C to 1.6°C	By Direct method
Measure Mode			
DC Resistance	0.00001 Ω	1.6 %	By Direct method
DC Resistance	0.0001 Ω to 1 k Ω 1 k Ω to 10 M Ω	0.9 % to 0.002 % 0.002 % to 0.006 %	By Direct method
DC High Resistance	0.1 M Ω to 500 G Ω 500 G Ω to 10 T Ω	0.03 % to 1.5 % 0.9 % to 1.25 %	By V/I Method
DC Voltage	1 mV to 10 V 10 V to 1000 V 1 kV to 15 kV	0.006 % to 0.002 % 0.002 % to 0.007 % 0.7 %	By Direct method
AC Voltage (50 Hz)	1 mV to 100 V 100 V to 750 V	0.9 % to 0.09 % 0.09 % to 0.04 %	By Direct method
DC Current	10 μA to 1000 A	0.03 % to 0.5 %	By Direct method
AC Current (50 Hz)	1 mA to 1 A	0.15 % to 0.3 %	By Direct method





High Precision Decade Resistance Box



Series: 7400

Features

• High precised, through highly reliable resistance element & skilled construction



- Calibration verification on 20 years stability data of the Master Calibration Standards
- CMC of the order of 0.002%
- Safety factor 1.25 is applied in designing
- 15 years maintainability assured.

Applications

- Calibration of RTD Temperature Indicators
- Load Cell and Strain Gauge Calibrations.
- All testing & calibration labs.
- Calibration of Speedo Meters.
- Meter calibrations.
- Calibration of Earth Resistance Meters

Technical Data

- Function
- Range/ Resolution
- Switches
- Switch Resistance
- Resistor Element
- Stability
 - Temperature Coefficient
 - Maximum Voltage to Case
 - Instrument Housing
 - Calibration Certificate (Optional)
 - Accessories (Optional)

: Calibration Resistance Standard

: 0.0001Ω to $111.1111111 K\Omega/0.0001\Omega$

: Silver/Gold plated, self wiping, spring loaded

: Insulated, Non Inductive, wire wound Manganin Wire

: I/3 of Accuracy (yearly)

: ≤10 ppm/°C

: 1000 volts

: Mild Steel with anti-rust powder coating

: ISO/IEC 17025 compliant or Factory Cal. Certificate.

: Carrying case & Connecting Cables.

	Resistance	Total	Max.	Max.	Max.	Accuracy:			
Decade	Per Step (Ω)	Resistance (Ω)	Current (A)	Voltage (V)	Power (W)	Ultra Precision	Precision	Standard	Economy
First	0.0001	0.001	20	0.002	0.04	±8%	±10%	±10%	±15%
Second	0.001	0.01	10	0.01	0.1	±5%	±8%	±10%	±15%
Third	0.01	0.1	4	0.04	0.16	±1%	±1%	±2%	±5%
Fourth	0.1	1.0	1.6	0.16	0.256	±0.2%	±0.2%	±0.5%	±1%
Fifth	1.0	10.0	800 m	0.8	0.64	±0.02%	±0.02%	±0.05%	±0.5%
Sixth	10.0	100.0	250 m	2.5	0.625	±0.01%	±0.02%	±0.05%	±0.5%
Seventh	100.0	1.0 k	80 m	8	0.64	±0.01%	±0.02%	±0.05%	±0.5%
Eighth	1.0 k	10.0 k	23 m	23	0.53	±0.01%	±0.02%	±0.05%	±0.5%
Ninth	10.0 k	100 k	7 m	70	0.49	±0.01%	±0.02%	±0.05%	±0.5%





Thumb Wheel Decade Resistance Box



Series: 7400A

Features

• High precised, through highly reliable resistance element & skilled construction



- Calibration verification on 20 years stability data of the Master Calibration Standards
- CMC of the order of 0.002%
- Safety factor 1.25 is applied in designing
- 15 years maintainability assured.

Applications

- Calibration of RTD Temperature Indicators
- Load Cell and Strain Gauge Calibrations.
- All testing & calibration labs.
- Calibration of Speedo Meters.
- Meter calibrations.
- Calibration of Earth Resistance Meters

Technical Data

Function : Calibration Resistance Standard

Range/ Resolution : 0.01 O to 99.9999999 MO/ 0.01 O

: Selectable Thumb Wheel with Gold plated Contacts **Switches**

Switch Resistance : $60 \text{ m}\Omega$

Resistor Element : Non Inductive Metal Film & Manganin Wire

Stability : I/3 of Accuracy (yearly)

Temp. Coefficient : Standard & Precision: 100 ppm/°C, Ultra Precision 50 ppm/°C

Instrument Housing : Mild Steel With Anti-rust powder coated

Maximum Voltage to Case : 2000 volts

Max. Voltage Capacity : 250 V DC & 176 VAC FSD

Calibration Certificate(Optional) : ISO/IEC 17025 compliant or Factory Calibration Certificate.

Accessories Optional : Carrying Case & Connecting Cables

Decade	Total Resistance	Max Power	Accuracy Standard		Accuracy Precision		Accuracy Ultra Precision	
(Ω)	(Ω)	(W)	individual DIAL	FSD	individual DIAL	FSD	individual DIAL	FSD
0.01	0.09		±15%		±15%		±10%	
0.1	0.9		±5%		±5%		±5%	
1.0	9.0		±1%		±1%		±1%	
10.0	90.0		±1%		±0.5%		±0.5%	
100.0	900	1	±1%	±1%	±0.5%	±0.5%	±0.1%	±0.1%
1.0 K	9.0 K	or	±1%		±0.5%		±0.1%	
10.0 K	90.0 K	2	±1%		±0.5%		±0.1%	
100.0 K	900.0 K		±1%		±0.5%		±0.1%	
1 M	9 M		±1.1%		±0.5%		±0.1%	
10 M	90 M		<u>+1%</u>		±0.5%		±0.1%	

05





Series: 7400SD

High Precision Decade Resistor Box



Features

• High precised, through highly reliable resistance element & skilled construction



- Calibration verification on 20 years stability data of the Master Calibration Standards
- CMC of the order of 0.002%
- Safety factor 1.25 is applied in designing
- 15 years maintainability assured.

Applications

- Calibration of RTD Temperature Indicators
- Load Cell and Strain Gauge Calibrations.
- All testing & calibration labs.
- Calibration of Speedo Meters.
- Meter calibrations.
- Calibration of Earth Resistance Meters

Technical Data

Function

• Range

Switches

• Switch Resistance

Resistor Element

Stability

Temperature Coefficient

Maximum Voltage to Case

Instrument Housing

Calibration Certificate (Optional)

: Calibration Resistance Standard

: 0.0001Ω to $10~M\Omega$

: Silver or Gold plated, self wiping, spring loaded

: ≤ 2 mΩ

: Insulated, Non Indective, wire wound Manganin Wire

: I/3 of Accuracy (Yearly)

: ≤ 10 ppm/°C upto $100k\Omega$ & 25 ppm > $100k\Omega$

: 1000 volts

: Mild Steel with anti-rust powder coating

: ISO/IEC 17025 compliant or Factory Calibration Certificate

Nominal Value (Ω)	Maximum Power	Max. Current	Max. Voltage	Max. Voltage Accuracy			
(52)	(W)	(A)	(V)	Ultra Precision	Precision	Standard	Economy
0.0001	0.04	20	0.002	±8%	±10%	±10%	±15%
0.001	0.1	10	0.01	±5%	±8%	±0.10%	±15%
0.01	0.16	4	0.04	±1%	±1%	±2%	±5%
0.1	0.256	1.6	0.16	±0.2%	±0.2%	±0.5%	±1%
1	0.64	800 m	0.8	±0.02%	±0.02%	±0.05%	±0.5%
10	0.625	250 m	2.5	±0.01%	±0.02%	±0.05%	±0.5%
100	0.64	80 m	8	±0.01%	±0.02%	±0.05%	±0.5%
1 K	0.53	23 m	23	±0.01%	±0.02%	±0.05%	±0.5%
10 K	0.49	7 m	70	±0.01%	±0.02%	±0.05%	±0.5%
100 K	10	10 m	1000	±0.01%	±0.5%	±0.5%	±5%
1 M	1	1m	1000	±0.01%	±0.5%	±0.5%	±5%
10 M	0.1	0.1 m	1000	±0.03%	±0.5%	±1%	±10%









High Value Decade Resistance Box



Series: 8400/8400HV

Features

- High precision through highly reliable resistance element & skilled construction
- Calibration verification on 20 years stability data of the Master Calibration Standards
- CMC of the order of 0.03% to 1.5%
- Safety factor 1.25 applied in designing
- 15 years maintainability assured.

Applications

For the calibration of:

- Insulation Testers upto 10 kV
- Megohm Meters
- Digital Meters
- Insulation Bridges
- Components comparison
- NABL Calibration Labs

Technical Data

- Function
- Range/ Resolution
- Switches
- Switch Resistance
- Switch Material
- Resistor Element
- Stability
- Temperature Coefficient
- Voltage Coefficient >5 kV
- Instrument Housing
- Maximum Voltage to Case
- Dielectric Voltage
- Calibration Certificate (Optional)
- Accessories (Optional)

- : Calibration Resistance Standard
- : $100 \text{ k}\Omega$ to $11.111111111 \text{ T}\Omega/100.0 \text{ k}\Omega$
- : Silver or Gold plated, self wiping, spring loaded
- : ≤ 5 mΩ
- : Glass Epoxy
- : Non Inductive, High Voltage, Epoxy Coated
- : I/3 of Accuracy (yearly)
- : $100 \text{ k}\Omega$ to $1.0 \text{ G}\Omega \leq 25 \text{ppm/°C}$, $1.0 \text{ G}\Omega$ to $1 \text{ T}\Omega \leq$
 - 100ppm/°C, above ITΩ 250ppm/°C
- : Upto I $T\Omega \leq 3ppm/volt \& above I T\Omega \leq 12ppm/volt$
- : Mild Steel with anti-rust powder coated
- : I kV for 8400 & 5/10 kV for 8400HV
- : 500 Volt AC for one minute
- : ISO/IEC 17025 compliant **or** Factory Cal. Certificate.
- : Carrying case & Connecting Cables.

Decede	Step	Total Resistance	Maximum Voltage (V)			Accuracy			
Decade	Resistance (Ω)	(Ω)	8400	8400-5 kV	8400-10 kV	Ultra Precision	Precision	Standard	Economy
First	100 k	1 M	1000	1000	1000	±0.01%	±0.5%	±0.5%	±2%
Second	1 M	10 M	1000	1000	1000	±0.01%	±0.5%	±0.5%	±2%
Third	10 M	100 M	1000	5000	5000	±0.03%	±0.5%	±1%	±3%
Fourth	100 M	1000 M	1000	5000	10000	±0.1%	±0.5%	±1%	±3%
Fifth	1 G	10 G	1000	5000	10000	±0.2%	±0.5%	±1%	±3%
Sixth	10 G	100 G	1000	5000	10000	±0.5%	±0.5%	±1%	±5%
Seventh	100 G	1 T	1000	5000	10000	±0.5%	±1.5%	±2%	±5%
Eight	1 T	10 T	1000	5000	10000	±3%	±3%	±5%	±10%
* Total Res	sistance Availa	ble: 11.111111 T	Ω						

ISO 17025 Compliant Calibration Facilities

07











Decade Resistor Box



8400 HVSD

Features

- · High precised, highly reliable element
- 20 years stability data of the Master Standards
- CMC of the order of 0.03% to 1.5%
- Safety factor 1.25 is applied in designing

Applications

For the calibration of:

- Insulation Testers > 10kV
- Megohm Meters
- Digital Meters
- Insulation Bridges

Technical Data

- Function
- Resistance Range
- Switches
- Switch Resistance
- Switch MaterialΩ
- Resistor Element
- Stability
- Temperature Coefficient
- Voltage Coefficient >5 kV
- Instrument Housing
- Maximum Voltage to Case
- Dielectric Voltage
- Calibration Certificate(Optional)
- Accessories (Optional)

- : Calibration Resistance Standard
- : I $k\Omega$ to $I0T\Omega$
- : Silver or Gold plated, self wiping, spring loaded
- : <5 mΩ
- : Glass Epoxy
- : Non Inductive, High Voltage, Epoxy Coated
- : I/3 of Accuracy (yearly)
- : ≤10ppm upto $10k\Omega$, $100 k\Omega$ to $1 G\Omega$ < 25ppm/°C,
 - $I G\Omega \text{ to } I T\Omega \leq I00ppm/^{\circ}C$, above $IT\Omega 250ppm/^{\circ}C$
- : Upto $IT\Omega \leq 3ppm/volt \& above <math>IT\Omega \leq 12ppm/V$
- : Mild Steel with anti-rust powder coated
- : I kV for 8400 & 5/10 kV for 8400HV
- : 500 Volt AC for one minute
- : ISO/IEC 17025 compliant or Factory Cal. Certificate.
- : Carrying case & Connecting Cables.

Nominal	Max	ximum V oltag	ge (In Volts)	Accuracy				
Value	8400	8400-5 kV	8400-10 kV	Ultra Precision	Precision	Standard	Economy	
1k	50	50	50	±0.01%	±0.02%	±0.05%	±0.5%	
10k	150	150	150	±0.01%	±0.02%	±0.05%	±0.5%	
1 M	1000	1000	1000	±0.01%	±0.5%	±0.5%	±2%	
10 M	1000	1000	1000	±0.01%	±0.5%	±0.5%	±2%	
100 M	1000	5000	5000	±0.03%	±0.5%	±1%	±3%	
1000 M	1000	5000	10000	±0.1%	±0.5%	±1%	±3%	
10 G	1000	5000	10000	±0.2%	±0.5%	±1%	±3%	
100 G	1000	5000	10000	±0.5%	±0.5%	±1%	±5%	
1 T	1000	5000	10000	±0.5%	±1.5%	±2%	±5%	
10 T	1000	5000	10000	±3%	±3%	±5%	±10%	





Decade Resistance/ Megohm Box



Series: 7484HV

Technical Data

• Function

• Range/ Resolution

Switches

Switch Resistance

Switch Material

Resistor Element

Stability

• Temperature Coefficient

• Voltage Coefficient >5 kV

• Instrument Housing

Maximum Voltage to Case

Dielectric Voltage

Calibration Certificate(Optional)

Accessories (Optional)

: Calibration Resistance Standard

: 0.0001 Ω to ||.|||||||||| $T\Omega$ / 0.0001 Ω

: Silver or Gold plated, self wiping, spring loaded

: \leq 2 m Ω upto X10k Ω & \leq 5 m Ω more than X10k Ω

: Glass Epoxy

: Non Inductive, High Voltage, Epoxy Coated

: I/3 of Accuracy (yearly)

: $10ppm upto 10k\Omega$, $100 k\Omega$ to $1.0 G\Omega$ < $25ppm/^{\circ}C$,

1.0 GΩ to $ITΩ \le 100$ ppm/°C,above ITΩ 250ppm/°C : Upto I $T\Omega \leq 3ppm/volt \& above I T\Omega \leq 12ppm/volt$

: Mild Steel with anti-rust powder coated

: I kV for 8400 & 5/10 kV for 8400HV

: 500 Volt AC for one minute

: ISO/IEC 17025 compliant or Factory Cal. Certificate.

: Carrying case & Connecting Cables.

	Step	Total	М	laximum Vol	tage	Accuracy:			
Decade	Resistance	Resistance	7484-1kV	7484-5 kV	7484-10 kV	Ultra Precision	Precision	Standard	Economy
First	0.0001	0.001	0.002	0.002	0.002	±8%	±10%	±10%	±15%
Second	0.001	0.01	0.01	0.01	0.01	±5%	±8%	±10%	±15%
First	0.01	0.1	0.04	0.04	0.04	±1%	±1%	±2%	±5%
Second	0.1	1.0	0.16	0.16	0.16	±0.2%	±0.2%	±0.5%	±1%
Third	1.0	10.0	8.0	0.8	8.0	±0.01%	±0.02%	±0.05%	±0.5%
Fourth	10.0	100.0	2.5	2.5	2.5	±0.01%	±0.02%	±0.05%	±0.5%
Fifth	100.0	1.0 k	8	8	8	±0.01%	±0.02%	±0.05%	±0.5%
Sixth	1.0 k	10.0 k	23	23	23	±0.01%	±0.02%	±0.05%	±0.5%
Seventh	10.0 k	100 k	70	70	70	±0.01%	±0.02%	±0.05%	±0.5%
Eighth	0.1 M	1 M	1000	1000	1000	±0.01%	±0.5%	±0.5%	±2%
Ninth	1 M	10 M	1000	1000	1000	±0.01%	±0.5%	±0.5%	±2%
Tenth	10 M	100 M	1000	5000	5000	±0.03%	±0.5%	±1%	±3%
Eleventh	100 M	1000 M	1000	5000	10000	±0.1%	±0.5%	±1%	±3%
Twelvth	1 G	10 G	1000	5000	10000	±0.2%	±0.5%	±1%	±3%
Thirteenth	10 G	100 G	1000	5000	10000	±0.5%	±0.5%	±1%	±5%
Fourteen	th 100 G	1 T	1000	5000	10000	±0.5%	±1.5%	±2%	±5%
Fifteenth	1 T	10 T	1000	5000	10000	±3%	±3%	±5%	±10%







Standard Resistor (Oil Cooled/Air Cooled)

Applications

For the Calibration of

- Earth Resistance Meter
- Micro/Mili Ohm Meter
- Ductor Tester
- RTD Temperature Indicators
 - Contact Resistance Meter · Kelvin Bridge
 - Multimeter
 - Load Cell and Strain Gauge







Series: 9409

Technical Data

Voltage Coefficient (Applicable above 5 kV)

: Calibration Resistance Standard **Function** : 0.000001 Ω to 100.0 $T\Omega$ Range

: Stain free non inductive Manganin coil/wire immersed in oil upto $100 \text{ k}\Omega$ **Resistor Element**

and >100 k Ω epoxy coated high voltage resistors, hermetically sealed

Stability : I/3 of Accuracy (yearly)

Temperature Coefficient : ≤ 10 ppm/°C upto $100k\Omega$, 25 ppm/°C from 0.1 M to 1.0 G Ω < 100 ppm/°C from 1.0 G to 1 T, 250 ppm/°C above 1T

: 3 ppm/volt \geq 100 k Ω to 1 T Ω ,12 ppm/volt > 1 T Ω

Instrument Housing : Metallic Container

Maximum Voltage to Case : 2000 volt

Dielectric Voltage : 500 volt AC for one minute

Terminals : Brass/Copper

Calibration Certificate (Optional) : ISO/IEC17025 compliant or Factory Calibration Certificate

Accessories (Optional) : Carrying case & Connecting Cables.

Туре	Resistance (Ω)	Maximum Current (A)	Max. Power Dissipitation (W)	Accuracy (±)
9409HP	0.000001	2000	4.0	5.0 %
9409HP	0.00001	2000	40.0	1.0 %
9409HP	0.0001	1000	100.0	0.5 %
9409A	0.001	31.6	1.0	0.1 %
9409B	0.01	10	1.0	0.05 %
9409C	0.1	3.16	1.0	0.02 %
9409D	1	1.0	1.0	0.01 %
9409E	10	0.316	1.0	0.01 %
9409F	100	0.1	1.0	0.01 %
9409G	1 k	0.0316	1.0	0.01 %
9409H	10 k	0.01	1.0	0.01 %
94091	100 k	3.16 m	1.0	0.05 %

Туре	Resistance (Ω)	Max. Voltage (V)	Accuracy (±)
9409J	1 M	1000	0.1 %
9409K	10 M	1k/5k/10k	0.5 %
9409L	100 M	1k/5k/10k	0.5 %
9409M	1 G	1k/5k/10k	1.0 %
9409N	10 G	1k/5k/10k	1.0 %
94090	100 G	1k/5k/10k	2.0 %
9409P	1 T	1k/5k/10k	5.0 %
9409Q	10 T	1k/5k/10k	5 %
9409R	100 T	1k/5k/10k	15 %





Micro & Milli - Ohm Meter Calibrator

Applications

For the Calibration of

- · Earth Resistance Meter
- Micro/Milli Ohm Meter
- Ductor Tester
- RTD / Temperature Indicators
- Contact Resistance Meter
- Kelvin Bridge
- Multimeter
- · Load Cell and Strain Gauge





Technical Data

Function

Resistance Range

Resistor Element

Stability

Temperature Coefficient

Instrument Housing

Maximum Voltage to Case

Dielectric Voltage

Terminals

Calibration Certificate(Optional)

Accessories (Optional)

: Calibration Resistance Standard

: 0.000001 Ω to 2 Ω

: Stain free, non Inductive Wire Wound Manganin wire,

immersed in oil

: I/3 of Accuracy (yearly)

 $: < 10 \text{ ppm/}^{\circ}\text{C}$

: Metallic Container

: 2000 volt

: 500 volt AC for one minute

: Brass/Copper


: ISO/IEC 17025 compliant or Factory Cal. Certificate

: Carrying case & Connecting Cables.

Resistance	Maximum Current			СМС	
(Ω)	(A)	Precision	Standard	Economy	СМС
0.000001	200	±3 %	±5%	±10%	
0.00001	200	±1 %	±2%	±5%	±3%
0.0001	200	±0.2%	±0.5%	±1%	to
0.001	31.6	±0.05%	±0.1%	±0.5%	±0.002%
0.01	10	±0.03%	±0.05%	±0.1%	or
0.1	3.16	±0.01%	±0.02%	±0.05%	Better
1.0	1.0	±0.01 %	±0.02%	±0.05%	
2.0	1.0	±0.01 %	±0.02%	±0.05%	











Fixed Value Insulation Tester Calibration System



Series: 9409FV

Features

- High precision through highly reliable resistance element & skilled construction
- 20 years stability data of the Master Standards
- CMC of the order of 0.03% to 1.5%
- Safety factor 1.25 applied in designing

Applications

For the calibration of:

- Meggers (upto 10 kV)
- Megohm Meters
- Insulation Testers
- Digital Meters
- Insulation Bridges

Technical Data

- Function
- Resistance Range/ Resolution
- Resistor Element
- Stability
- Temperature Coefficient
- Voltage Coefficient >5 kV Instrument Housing
- Maximum Voltage to Case
- Dielectric Voltage
- Calibration Certificate(Optional)
- Accessories (Optional)

- : Calibration Resistance Standard
- : $Ik\Omega$ to $20T\Omega/Ik\Omega$
- : Non Inductive, High Voltage, Epoxy Coated
- : I/3 of Accuracy (yearly)
- : $10ppm upto 10k\Omega$, $100 k\Omega$ to $1.0 G\Omega$ < $25ppm/^{\circ}C$, I.0 GΩ to I TΩ ≤ I00ppm/°C, above ITΩ 250ppm/°C
- : Upto I $T\Omega \leq 3ppm/volt \& above I T\Omega \leq 12ppm/volt$
- : Mild Steel with anti-rust powder coated
- : I kV/5kV/10kV
- : 500 Volt AC for one minute
- : ISO/IEC 17025 compliant or Factory Cal. Certificate.
- : Carrying case & Connecting Cables.

Nominal Value	Maxim	num Voltage	(V)		Accurac	у	
(Ω)	9409FV-1kV	9409FV-5kV	9409FV-10kV	Ultra Precision	Precision	Standard	Economy
1 k	50	50	50	±0.01%	±0.02%	±0.05%	±0.5%
10 k	150	150	150	±0.01%	±0.02%	±0.05%	±0.5%
0.1 M	1000	1000	1000	±0.01%	±0.5%	±0.5%	±2%
1 M	1000	1000	1000	±0.01%	±0.5%	±0.5%	±2%
10 M	1000	5000	5000	±0.03%	±0.5%	±1%	±3%
100 M	1000	5000	10000	±0.1%	±0.5%	±1%	±3%
1 G	1000	5000	10000	±0.2%	±0.5%	±1%	±3%
10 G	1000	5000	10000	±0.5%	±0.5%	±1%	±5%
100 G	1000	5000	10000	±0.5%	±1.5%	±2%	±5%
1T	1000	5000	10000	±3%	±3%	±5%	±10%
10 T	1000	5000	10000	±5%	±3%	±5%	±10%
20 ΤΩ	1000	5000	10000	±8%	±10%	±10%	±15%





Air/Oil Cooled DC Shunt









9410

Technical Data

Function

Current Range

Resistor Element

Stability

Temperature Coefficient

Instrument Housing

Maximum Voltage to Case

Dielectric Voltage

Terminals

Calibration Certificate (Optional)

Accessories (Optional)

Calibration Current/ Resistance Standard

: upto 20000 Amperes

: Stain free, Manganin strip/wire

1/3 of Accuracy (yearly)

< 10 ppm/°C

: Mild Steel Sieve for Air Cooled & Metallic Container for Oil immersed

: 500 volt AC for one minute

: Brass/Copper

: ISO/IEC 17025 compliant or Factory Calibration Certificate

: Carrying case & Connecting Cables.

Current (A)	Resistance (Ω)	Voltage Drop (V)	Wattage (W)	Accuracy	NABL Compliant CMC (±)
1.5	1.0	1.5	2.25	± 0.05 %	
5	0.2	1.0	5.0	± 0.05 %	
15	0.1	1.5	22.5	± 0.05 %	
15	0.01	0.15	2.25	± 0.05 %	
50	0.01	0.5	25.0	± 0.05 %	
50	0.02	1.0	50.0	± 0.05 %	
75	0.002	0.15	11.25	± 0.05 %	
150	0.01	1.5	225.0	± 0.5 %	±1.6%
150	0.001	0.15	22.5	± 0.5 %	to
300	0.001	0.3	90.0	± 0.5 %	±0.002%
500	0.0002	0.10	50.0	± 0.5 %	or
750	0.0002	0.15	112.5	± 1.0 %	Better
1000	0.0001	0.1	100.0	± 1.0 %	
1500	0.0001	0.15	225.0	± 1.0 %	
2000	0.00005	0.1	200.0	± 1.0 %	
5000	0.00002	0.1	500.0	± 1.0 %	
5000	0.000001	0.005	25.0	± 5.0 %	5% Non NABL
20000	0.000001	0.02	400	± 5.0 %	5% Non NABL

Applications

For the calibration & Testing of

- Battery Testing
- Earth Resistance Meter
- Micro/Mili Ohm Meter
- Ductor Tester
- RTD / Temperature Indicators
- Load Bench/Power Supply
- Contact Resistance Meter
- Kelvin Bridge
- Multimeter
- · Load Cell and Strain Gauge





Decade Capacitance Box



Series: 7500

Features

- High accuracy upto ±0.5%
- Low zero capacitance: ≤ 3 pF/Switch
- Output: 5-Terminal construction Or BNC
- Stability 100 ppm/year
- Excellent TC 50 ppm/°C

Applications

- Calibration of LCR Meters
- Calibration of Capacitance Meter
- General purpose capacitance substitution.
- Finding optimal operating values in circuits.
- Service work, troubleshooting and maintenance.

Technical Data

- Function
- Capacitance Range
- Resolution
- Switches
- Switch Capacitance
- Capacitor Element
 - Stability
 - Temperature Coefficient
 - Instrument Housing
 - Maximum Voltage to Case
 - Dielectric Voltage
 - Calibration Certificate(Optional)
 - Accessories (Optional)

- : Calibration Capacitance Standard
- : IpF to II.IIIIII mF
- : IpFΩ
- : self wiping, better Quality Rotary switches
- : ≤ 3 pF
- : Fix Value Capacitors
- : I/3 of Accuracy (yearly)
- : 50ppm/°C
- : Mild Steel with anti-rust powder coated
- : 2000 volts
- : 500 Volt AC for one minute
- : ISO/IEC 17025 compliant or Factory Cal. Certificate.
- : Carrying case & Connecting Cables.

Docado l'ottil Deciliae		Maximum Voltage	Accuracy			Accuracy
(In F)	Capacitance (In F)	(V)	Precision	Standard	Economy	Certified@
1p	10p	250	± 4%	± 5%	± 10%	1 kHz
10p	100p	250	± 2%	± 3%	± 5%	1 kHz
100p	1000p	250	± 1%	± 2%	± 4%	1 kHz
1n	10n	250	± 0.5%	± 1%	± 2%	1 kHz
10n	100n	250	± 0.5%	± 1%	± 2%	1 kHz
100n	1000n	250	± 0.5%	± 1%	± 2%	1 kHz
1μ	10µ	250	± 0.5%	± 1%	± 2%	1 kHz
10µ	100µ	250	± 0.5%	± 1%	± 2%	1 kHz
100µ	1000µ	250	± 0.5%	± 1%	± 2%	1 kHz
1m	10m	250	+ 0.5%	+ 1%	+ 2%	1 kHz









Decade Inductance Box



Series: 7600

Features

- High accuracy upto ±0.5%
- Low zero Inductance
- Output: 5-Terminal construction Or BNC
- Stability 100 ppm/year
- Excellent TC 50 ppm/°C

Applications

- Calibration of LCR Meters
- Calibration of Inductance Meter
- General purpose inductance substitution.
- Finding optimal operating values in circuits.
- Service work, troubleshooting and maintenance.

Technical Data

- Function
- Inductance Range
- Resolution
- Switches
- Switch Capacitance
- Inductance Element
- Stability
- Temperature Coefficient
- Instrument Housing
- Maximum Voltage to Case
- Dielectric Voltage
- Calibration Certificate(Optional)
- Accessories (Optional)

vaiseshika@gmail.com

- : Calibration Inductance Standard
- : 10μH to 10 μH
- : Self wiping, better quality rotary switches,
- : ≤ 3 pF
- : Wire wound inductors
- : I/3 of Accuracy (yearly)
- : 50ppm/°C
- : Mild Steel with anti-rust powder coated
- : 2000 volts
- : 500 Volt AC for one minute
- : ISO/IEC 17025 compliant or Factory Cal. Certificate.
- : Carrying case & Connecting Cables.

Decade Total Decade			Accuracy			Accuracy	
/	Inductance (In H)	Voltage (V)	Precision	Standard	Economy	Certified@	
Ι0μ	Ι00μ	1	± 0.5%	± 0.7%	± 1%	1 kHz	
100μ	1000μ	1	± 0.5%	± 0.7%	± 1%	1 kHz	
Im	I0m	1	± 0.5%	± 0.7%	± 1%	1 kHz	
I0m	100m	1	± 0.5%	± 0.7%	± 1%	1 kHz	
100m	1000m	1	± 0.5%	± 0.7%	± 1%	1 kHz	
I	10	1	± 0.5%	± 0.7%	± 1%	1 kHz	







AC/DC High Voltage Probe



840 I

Features

- Glass Epoxy Case to avoid Voltage Shock
- Compatibility with 4.5, 5.5 & 6.5 DMM
- Output Ratio: 1000: I

Applications

- Calibration of High Voltage Sources
- Measurement of Voltage above I kV
- Step Down High Voltage Measurement

Technical Data

Function : Calibration Voltage Standard

100 Volt to 15 kilo Volts Range **Accuracy** 1% in DC & 2.5% in AC

Stability : I/3 of Accuracy (Yearly)

Input Impedance ≥ 1000 MΩ

Traceability Drift : 0.06%

Construction/ Housing Case : Portable in Glass Epoxy Material

Maximum Voltage to Case : 15 kV

Cable Length : I Meter

: 0°C to 50°C **Operating Temperature** : -10°C to 60°C **Storage Temperature**

: ISO/IEC 17025 compliant or Factory Cal. Certificate. **Calibration Certificate (optional)**

Input Voltage	Loading Current	Output Voltage
1 kV	0.1 μΑ	1 V
5 kV	0.5 μΑ	5 V
10 kV	1 μΑ	10 V
15 kV	1.5 µA	15 V











What the Eminent Experts say about us

Prof.S.G.Damle Vice Chancellor, Maharishi Markandeshwar University, Mullana, Ambala

It is an immense pleasure to visit Vaiseshika come here is a pleasure for two reasons. Metrology Laboratory, Ambala Cantt. Really it is an One -to see an institution so devoted to On the occasion of the XI Commonwealth amazing experience to notice the devotion, quality and high standards. Two -to see the India Small Business Programme, I had the dedication and commitment of the organization. personal development of Dr. Anil Jain to pleasure of visiting the unit along with a lot They have designed indigenous technology, which become a leading & highly respected delegation of 70+ delegations from 35 is of superb quality & also of international standard. entrepreneur.We can only say"God Speed" commonwealth countries. We were All the equipment are standardized following the &"Good Luck" and look forward to visiting inspired by the work and leadership of this standardized norms and parameters.The scientific your"international class" facility in the near company. Dr. Anil Jain is a true embodiment equipments, devices of Vaiseshika organization will future! be really boon to research professional in technical and health science stream (researchers). I extend my congratulations & best wishes to their efforts.

Mr. Krishnendu Jana Scientist 'F' Group Director (HR & QA) & MR Integrated Test Range (ITR), Chandipur, Balasore (Orissa)

I am really happy for the hospitality and cocooperativeness by the management & staff of Vaiseshika Electron Devices. The quality of standards for ITR which are checked were found excellent. It is neat and clean organization and doing excellent work for the service of the Nation. I also came to know that the organization is dedicated and by their innovative ideas have achieved great success in the field of Calibration and making standards for Calibration.

Dr.B. Murali United Nations Development Programme, Adviser & Head New Delhi


Having visited Vaiseshika's old facilities, to London, UK

Mr. Ram Venuprasad Enterprise & Agriculture Commonwealth Secretariat

of Jai Ho!

People like Mr. Jain make me proud to be an Indian. lai Hind.

Message for every Indian



Prestigious Industrial Organizations using Vaiseshika Standards

































































Applications of Resistance Calibration Standards in Industry & Metrology Laboratories


by Praveen Jain, **B.E** (Honours)

CEO, Vaiseshika Electron Devices, Ambala Cantt.

High Precision Decade Resistance Box, High Resistance Decade Megohm Box , Milli & Micro-Ohm meter Calibrator, Standard Resistor, Fixed Value Insulation Tester Calibration System, Shunt, Capacitance & Inductance Box, are the major calibration standards offered by Vaiseshika for the ISO 17025:2017 Metrology Laboratories. Here are the glimpses of the various applications for your study:

I. Calibrating an RTD Transmitter:


A resistance box can be used as a RTD simulator to provide standard values of resistance for simulation and calibration. RTD simulators provide a resistance simulating the output of a resistance temperature detector (RTD) at a particular temperature.



Connection Diagram of a Resistance Box to a Transmitter

2. Calibrating RTD based automobile Panel Meters:

In automotive industry these are used for the testing and calibration of speedometers. Today speedometers are having electronic circuit to display the speed of the automobile. Therefore feeding predetermine values of precision resistance in the input of the speedometer will be used to calibrate the speedometers.










3. Calibrating Insulation Testers:

The High Value Decade Resistance Boxes are used in the precise calibration of Meggers, Insulation Testers, Insulation Bridges, Megohm Meters, Digital Meters and Components Comparison.

These Boxes are having high voltage rating. This helps in calibration of the above mentioned instruments with latest technology and high voltages upto 10,000 V DC (Resistance from 0.1 Meg Ohm to 10 Tera Ohm).



Calibration setup of a High Value Decade Resistance Box for Insulation Tester

4. Calibrating Micro Ohm Meters and Milli Ohm Meters:

Vaiseshika Milli & Micro Ohm Meter Calibrator can be used by quality control and quality assurance laboratories in manufacturing, plant maintenance and filed use to calibrate your micro ohm meters and milli ohm meters using the four wire Kelvin Measurement Method. Vaiseshika Calibrators can simulate low resistance and check accuracy and reliability of bench top, portable handheld meters with various resolutions, ranges, accuracies and operational modes involving the safety, quality and cost implications for reporting consistently accurate results in the digital milli ohm meters and micro ohm meters.



Calibration setup for Micro ohm Meter Calibration

www.vaiseshika.com

19






5. Shunt Calibration of Strain Gage Sensor (Load Cell):

Since a strain gage load cell is a passive electrical device, there exists a simple, yet effective, method for checking the calibration of a load cell system in the field or when a means of applying actual forces is unavailable. Inducing an electrical imbalance in the cells bridge circuit will simulate the bridge imbalance caused by the application of actual forces to the load cell. Then the system gain may be adjusted so that the system output signal or display indicates a known force on the load cell.

To perform a Shunt Calibration, use the following procedure:

- I. Remove or Stabilize all forces on the load cell.
- 2. Adjust the display or indicator ZERO to read exactly zero.
- 3. Connect the Shunt Calibration Resistor to the Terminals specified on the Calibration Certificate, and adjust the SPAN or GAIN until the display reads the force value stated on the Certificate.
- 4. Repeat the procedure to insure a valid Calibration.


Shunt calibration is accepted throughout the industry as means of constant calibration of a signal conditioner and transducer between calibrations of known, applied, traceable, mechanical, input values. It's important to remember that the shunt resistor can simulate either a tension or compression input in the Wheatstone Bridge.



Thermal EMF and TCR errors can affect the process and should be minimized by choosing a proper resistor. The shunt calibration can be applied conveniently and at any moment and most important during the test programs.

Consequently, strain-gage and transducer manufacturers supply shunt calibration data, along with a shunt calibration precision resistor, as a standard feature. Of course, regular physical calibration is recommended as well to ensure the accuracy, stability, reliability and linearity of the instrument itself.

Shunt-calibration resistors are chosen to accurately simulate resistance change in a strain gage subjected to specified levels of compressive strain. Strain indicators generally will produce a linear output with a fully active half-bridge or fullbridge input circuit, and will be slightly in error when a single active arm is used. The same nonlinearity occurs whether the gage is actually strained in compression or simulated by shunting the gage with the corresponding calibration resistor








6. Estimating the Charging and Discharging Rate of a Battery:

Air Cooled DC Shunt is also used for fast and controlled Discharging of Batteries.

The battery capacity, that battery manufacturers print on a battery, is usually the product of 20 hours multiplied by the maximum constant current that a new battery can supply for 20 hours at 68 F° (20 C°), down to a predetermined terminal voltage per cell. A battery rated at 100 A·h will deliver 5 A over a 20 hour period at room temperature.

However, if it is instead discharged at 50 A, it will have a lower apparent capacity to last for two hours.

The Vaiseshika DC Shunt is the heart of the below mentioned circuit which is used to verify the ampere-hour capacity of the battery:



Discharging of Battery using Vaiseshika DC Shunt

The charge and discharge current of a battery is measured in C-rate. Most portable batteries are rated at IC. This means that a 1000mAh battery would provide 1000mA for one hour if discharged at IC rate. The same battery discharged at 0.5C would provide 500mA for two hours. At 2C, the 1000mAh battery would deliver 2000mA for 30 minutes. IC is often referred to as a one-hour discharge; a 0.5C would be a two-hour, and a 0.1C a 10- hour discharge When discharging a battery with Vaiseshika DC Shunt that allows the setting of different discharge C-rates, a higher capacity reading is observed if the battery is discharged at a lower C-rate and vice versa. By discharging the 1000mAh battery at 2C, or 2000mA, the analyzer is scaled to derive the full capacity in 30 minutes The manufacturer plots the voltage versus the discharge time curve. Using this curve the rated capacity is verified.

Vaiseshika DC Shunts can be used for the testing and calibrations of Charger / Discharger Panel Meters, Battery Testers, Battery Performance Testing Devices, Clamp-on-Meters, Insulation Testers and Tong Testers.

Vaiseshika Air Cooled DC Shunt is also used as a Reference Calibration/Master Standard for comparing and calibrating the Battery Discharging Resistors/Rheostats (of the manufacturers) at their workshops.

Air Cooled DC Shunt is also used for measuring the specification of transformer like its power, voltage and current.





National Awards




National Award for Quality Products From President of India




National Award for Entrepreneurship from Prime Minister of India

Appreciation & Satisfaction Letters



SHAR Space Centre, Sriharikota









Discover More When You Go Online @ www.vaiseshika.com



Spectrum of Optical Instruments























Vaiseshika Electron Devices



38-Industrial Estate, Across Tangri River Bridge,

Ambala Cantt.- 133 001 (INDIA)

Phones: (0171)-2699827, 9991157781





www.vaiseshika.com 🔀 vaiseshika@gmail.com



QR Code for Vaiseshika **Resistance Standards Catalog**